

Accessories



Features & Advantages

- ▶ Its air tightness passed rigorous smoke isolation test in the close state.
- ▶ It can be linked with the fan motor to realize zero wind resistance operation in the fully open state.
- ▶ Strong pressure resistance, can long-term bear strong wind making by high negative pressure fan without deformation.
- ▶ High-strength plastic coupling and aluminum alloy body, with anti-corrosion to be adapted to all kinds of harsh animal husbandry environment, or marine environment.
- ▶ Length and width can be customized according to demands.

Electric rolling door



When reaches the positioning,
the motor power is cut off and self-locking

Model No.		JMN18"	JMN24"	JMN36"	JMN50"	JMN51"	JMN57"
Motor data	Volts (V)	220	220	220	220	220	220
	Hertz (HZ)	50 60	50 60	50 60	50 60	50 60	50 60
	Rated current (A)	0.64	0.64	0.99	0.99	0.99	0.99
	Power (W)	145	145	228	228	228	228
	Operation time consuming (S)	Full open	11	14	19	23	24
Full closed		11	14	19	23	24	26
Features	Frame	Aluminium alloy					
	Shutter piece	PVC					
	Bracket	Coated steel					
Overall dimensions (mm)		950*1170*255	1130*1350*255	1430*1715*255	1790*2010*255	1830*2050*255	1980*2200*255
Opening dimensions (mm)		730*730	910*910	1270*1270	1570*1570	1610*1610	1760*1760